

# SPEEDWAY® PRE-GALV. CABLE LADDER SYSTEMS

## Ladder Fixing Kit



Code

VSEK/QQ

Sold in packs of 8.

## Earth Braid



Designed for use in installations where an additional means of earthing or electrical bonding is specified.  
Comprised of a 16mm<sup>2</sup> tinned copper braid crimped into M10 tinned copper end connectors.  
The Speedway® Earth Braid/Bonding Strap is compatible with Speedway® SW4, SW5 & SW6.

Code	Description
EBS-01	M10 Braid (suitable for SW5 & SW6)
EBS-M8-01	M8 Braid (suitable for SW4)

Pre-punched holes for fixing the earth bonding strap are located at each end of the ladder and fittings.

## Standard Material Gauges & Loading Data

Ladder Type	Material & Finish	Sidewall Gauge (mm)	Rung Gauge (mm)						Loading Capacity (kg/m)				
			150	300	450	600	750	900	1.0m span	1.5m span	2.0m span	2.5m span	3.0m span
Speedway® SW4	QQ	1.5	1.5						233	233	233	233	233
Speedway® SW5	QQ	1.5	1.5						234	234	234	234	234
Speedway® SW6	QQ	1.5	1.5						235	235	235	235	235

QQ - Pre-Galvanised Steel

The Speedway® cable ladder system is also available in a combination of side wall gauges (1.5mm & 2.0mm) and rung gauges (1.5mm, 2.0mm, 2.5mm) to suit specific installation requirements.

Consult our Design Team for guidance on the correct selection of material gauge combinations.

## Cable Ladder Lighting Accessories

See page 79 for a full range of Lighting Accessories compatible with Speedway® Cable Ladder.

